

# Specifications — PS 150 Power Supply

---

## Specifications

Power input.....	100VAC to 240VAC, 50/60 Hz, internal, 100 watts
Power output.....	(6) 15VDC outputs (maximum current of all outputs 5.0 A)
Temperature/humidity.....	Storage -40° to +158°F (-40° to +70°C) /10% to 90%, non-condensing Operating +32° to +113°F (0° to +45°C) /10% to 90%, non-condensing
Cooling .....	Convection, vents on left and right sides
Mounting	
Rack mount .....	Yes, with optional 1U, 9.5" deep rack shelf, part #60-190-01 (RSU 129) or 60-604-01 (RSB 129)
Furniture mount.....	Yes, with optional under-desk mounting kit, part #70-222-01 (MBU 149)
Enclosure type .....	Metal
Enclosure dimensions.....	1.75" H x 4.4" W x 8.5" D (1U high, quarter rack width) (4.4 cm H x 11.2 cm W x 21.6 cm D)
Product weight .....	1.2 lbs (0.5 kg)
Shipping weight.....	3 lbs (2 kg)
Vibration.....	ISTA/NSTA 1A in carton (International Safe Transit Association)
Regulatory compliance	
Safety.....	CE, CUL, UL
EMI/EMC .....	CE, C-tick, FCC Class A, ICES, VCCI
MTBF.....	30,000 hours
Warranty.....	3 years parts and labor

**NOTE** Specifications are subject to change without notice.

7.6-102708-D3